

FATH®

FATH®

SECURE
INTEGRATABLE

The RELIABLE access control system

INDIVIDUAL
ELECTRONIC

TANlockZero



FATH Mechatronics GmbH
Gewerbepark Hügelmühle 31
91174 Spalt
Germany

+49 9175 7909-152



info@tanlock.com
www.tanlock.com

@fath.mechatronics
@f_mechatronics
@fathmechatronics



WWW.TANLOCK.COM

SIMPLY SAFE RACKS.

TANlock Zero

The simple way to secure your infrastructure.

high versatility

The **TANlock Zero** has many different solutions for various sectors, besides data centers to protect sensitive data and ensure security in the digital age.



Features:

- Emergency power supply
- Connection to SPS
- Various authentication technologies
- Easy integration
- Safe



Easy integration

The **TANlock Zero** is system-independent, as no additional software is required. Thus, it can also be effortlessly integrated into already existing infrastructures.



Compatible

Due to its control via 5V, 12V or 24V, the **TANlock Zero** can be easily integrated into existing IT infrastructures. No server cabinets from specific manufacturers are required and various adapters make it compatible with almost all server cabinets.

INDIVIDUAL AUTHENTICATION

FATH®



Remote

- Can be operated remotely



RFID

- Authentication via RFID (13.56 MHz)
- Legic, HID iCLASS, Mifare Desfire EV1, EV2
- BLE (Bluetooth Low Energy)
- Either local or via Wiegand with central user administration



PIN + RFID

- Two-factor authentication via PIN and RFID (13.56 MHz) possible
- Legic, HID iCLASS, Mifare Desfire EV1, EV2
- BLE (Bluetooth Low Energy)



Finger print + RFID

- Two-factor authentication via finger print and RFID (13.56 MHz) possible
- Legic, HID iCLASS, Mifare Desfire EV1, EV2
- BLE (Bluetooth Low Energy)



Touch display + RFID

- Authentication by input on the touch display or via RFID (13.56 MHz)
- Legic, HID iCLASS, Mifare Desfire EV1, EV2
- BLE (Bluetooth Low Energy)
- Configurable display